

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

No. FP170 Range Collar – 20220107

P1/3

- 1. Unique identification code of the product-type:** Nullifire FP170 Range Collar
- 2. Intended use/es:** These are pipe closure devices used to form penetration seals where combustible pipes, cables and metal pipes with insulation penetrate walls and floors.
- 3. Manufacturer:** TREMCO CPG UK Limited, Coupland Road, Hindley Green, Wigan, WN2 4HT
- 4. Authorized representative:** Tremco CPG Netherlands B.V., Vlietskade 1032, NL-4241 WC Arkel
- 5. System/s of AVCP:** System 1
- 6. European Assessment Document:** EAD 350454-00-1104
European Technical Assessment: ETA 21/0183
Technical Assessment Body: ETA-Danmark A/S
Notified Body: 2821, UL International (NL) B.V.

7. Declared performance/s:

Basic Work Requirement	Performance
Mechanical resistance and stability	
None	Not relevant
Safety in case of fire	
Reaction to fire (EN 13501-1)	Class E
Resistance to fire (EN 13501-2)	See ETA 21/0183 Annex A
Hygiene, Health and the Environment	
Air Permeability (EN 1026:2000)	NPD
Water Permeability EAD 350454-00-1104	NPD
Release of dangerous substances	Use categories: IA1, S/W3 Declaration of manufacturer
Safety in Use	
Mechanical Resistance and stability (EOTA TR001:2003)	NPD
Resistance to Impact / movement (EOTA TR001:2003)	NPD
Adhesion	NPD
Protection against noise	
Airborne Sound Insulation (EN10140-2 / EN ISO 717-1)	NPD
Energy, Economy and Heat Retention	
Thermal Properties (EN 12664, EN 12667 or EN 12939)	NPD
Water vapour permeability (EN ISO 12572 / EN 12086)	NPD
General Aspects Relating to fitness for use	
Durability and Serviceability (EOTA TR 024:2009)	Y ₂

The performance of the product identified above is in conformity with the set of declared performance/s. This

P2/3

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

M. Liptrot, Operations Director



At Wigan on 07.01.2022

Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

CE	
TREMCO CPG UK Limited, Coupland Road, Hindley Green, Wigan. WN2 4HT UK 21 2821-CPR-0128 FP170 Range Collar – 20220107 www.nullifire.com/FP170/	
EN 1366-3: 2009 ETA 21/0183 EAD 350454-00-1104	
These are pipe closure devices used to form penetration seals where combustible pipes, cables and metal pipes with insulation penetrate walls and floors.	
Essential Characteristic	Performance
Safety in Case of Fire	
Reaction to fire	Class E
Resistance to fire	See ETA 21/0183 Annex A
Hygiene, Health and Environment	
Air Permeability (EN 1026:2000)	NPD
Release of dangerous substances	Use categories: IA1, S/W3 Declaration of manufacturer
Safety in use	
Mechanical resistance and stability	NPD
Resistance to impact/movement	NPD
Adhesion	NPD
Protection against noise	
Airborne sound insulation	NPD
Energy, Economy and Heat Retention	
Thermal properties	NPD
Water vapour permeability	NPD
General aspects relating to fitness for use	
Service & Durability	Y ₂