

Apollo (A6546)



Water-Based Panel Bonding Adhesive

Apollo (A6546) has been specifically developed for a wide range of panel bonding applications, including fixing batons and uPVC wall panels directly onto vertical substrates without any mechanical fixings. It is a single component solvent-free water-based adhesive that offers the manufacturer many benefits.

Benefits:

- **Extremely versatile:** bonds a wide range of materials.
- **Minimises task-time:** quickly and easily applied with a notched trowel or scraper
- **High initial grab:** bond panels directly to walls with no other fixings
- **Peace of mind:** Excellent bond strength and gap filling properties
- **Green credentials:** solvent-free

Technical Data

Base	Synthetic Elastomer	Shelf Life	12 months
Appearance	White	Storage	5-25°C
Temperature Resistance	-20-70°C	Health & Safety	See MSDS
Coverage	10m² per 12kg tub	Cleaner	Water when wet
Application Temperature	5-25°C	Viscosity CPS	Thixotropic Paste



Apollo Chemicals Limited
Sandy Way, Amington Industrial Estate,
Tamworth, Staffordshire, B77 4DS

Tel: +44 (0)1827 54281
Fax: +44 (0)1827 53030

Email: enquiries@apolloadhesivesolutions.co.uk
www.apolloadhesivesolutions.co.uk

Tel: 01 – 885 00 00

www.ect.ie

info@ect.ie

Apollo (A6546)



Instructions for Use:

1. Ensure surfaces to be bonded are clean and free from grease and other contaminants.
2. Apply an even coat of (A6546) to the panel/substrate using a notched trowel or scraper.
3. Immediately press the panel firmly to the wall/substrate to ensure adequate adhesive transfer.
4. Allow the bonded item a minimum of 24 hours to ensure a secure bond.

General Notes

Apollo (A6546) is a water based adhesive and should not be used or stored in temperatures below 5°C to protect from frost.

Apollo (A6546) is supplied in 12kg tubs, with coverage of 10m² per 12kg tub when applied using a 5mmx5mm square notched trowel.

IMPORTANT NOTES

Storage and handling: The product should be stored unopened in a dry condition at a temperature of 5-25°C. This will ensure the stated shelf-life. The adhesive will have a limited life once the container is opened.

Temperature and timings: All information on temperature and timings represent normal working conditions and is provided as a guideline only. However, please contact Apollo for advice if you wish to operate outside of these parameters.

Disclaimer: Apollo has taken care to ensure that the information provided in the literature is correct and up to date. However, it is not intended to form any part of a contract or provide a guarantee. Purchasers/intending purchasers should contact Apollo to check whether there have been any changes to the information since publication of the literature. Please ensure you have read the hazard labels and material safety data sheet before using this product.



Apollo Chemicals Limited
Sandy Way, Amington Industrial Estate,
Tamworth, Staffordshire, B77 4DS

Tel: +44 (0)1827 54281
Fax: +44 (0)1827 53030

Email: enquiries@apolloadhesivesolutions.co.uk
www.apolloadhesivesolutions.co.uk