

Pafra Adhesives Ltd Bentalls, Basildon, Essex, SS14 3BU

Telephone +44 (0) 1268 290610
Fax +44 (0) 1268 290619
Email enquiries@pafra.com
Website www.pafra.com

AquaPAL® 9254 Lay Flat Laminating Adhesive

Issue 9 09/11/2016

AquaPAL® 9254 is a laminating adhesive, for use on all types of laminators, which combines the best properties of a high quality good lay-flat laminating product with the cost-effectiveness of a standard product. The unusual slow drying properties allows the board to equalise before fibre tear development, reducing curl to a minimum. The high solids content reduces the level of moisture added to board during laminating which further improves lay flat and minimises blistering.

Features & Benefits

- Excellent lay-flat
- Low even coat weight
- Easy clean
- Deep Fibre Tear
- Suitable for a wide range of substrates
- Good milage

AquaPAL® 9254 is cost effective in use as it is possible to apply low and even coat weights.

Technical Data

 Viscosity:
 $10.0\text{-}12.0 \text{ Poise } @ 50.7 \text{ sec}^{-1}$ pH:
 ~7.7

 Solids:
 57.5-60.5% sg (20 °C)
 1.20

 Brookfield 3/20/25:
 2000 centiPoise Colour:
 Cream

Application Details

AquaPAL® 9254 is designed specifically for use with roller coater application systems.

Storage & Shelf Life

For optimum performance use within 5 Months. Store between 5-30 °C and protect from freezing. Stir or shake before use.

Health & Safety

Users should familiarise themselves with the safety data sheet before using or handling this product.

Regulatory

Every precaution has been taken in the design of this adhesive to ensure it safe for the consumer.

Tel: 01 – 885 00 00 www.ect.ie info@ect.ie

