

Technical Data Sheet

Release Agent LPZ/II



- Product name:** LPZ/II
- Area of application:** Before pre-milling (edgebanding)
- Application:** Spray onto the upper and lower edge area of the workpiece. Prevents the adhesion of emerging glue onto the workpiece.

Physical and chemical characteristics:

- Form: Liquid
- Colour: Colourless
- Smell: Alcohol-like
- Ignition temperature: 425 °C
Product is not selfigniting.
- Melting point: -100 °C
- Boiling range: ≥ 78 °C
- Flash point: ~13 °C
- Values for explosion: Lower 3,5 Vol %
Upper 15,0 Vol %
Product is not explosive.
(formation of explosive air/steam mixtures is possible)
- Density: ~ 0,79 g/cm³ (at 20°C)
- Vapour pressure: 59 hPa (at 20°C)
- VOC: 96% volatile organic compounds



Composition: Mixture of ethanol

Available packaging (litre): 10|30|200|1000

Safety Instructions:

- Transport: Class 3, PG II
 - Customs tariffe : 38140090
 - Storage: Keep container tightly closed. Store in a cool, dry place.
 - Shelf life: Unlimited shelf life when stored properly
 - Disposal: According to official regulations, or returnable packaging
-
- ✓ Low consumption: <1 litre per fine nozzle per 5000 running metres
 - ✓ Compatible with all commercially available edge bands and adhesives
 - ✓ Finish Quality
 - ✓ High-quality raw materials
 - ✓ Not harmful to the environment or Health

Tel: 01 – 885 00 00

www.ect.ie

info@ect.ie

All information in this document is based on current knowledge and experience. The user is not released from his own tests and trials. We accept no liability for damage resulting from improper use.