

Application chart

- Official recommendation list for edgebanding
- Approved and qualified by Holz-Her GmbH



Jowatherm® | EVA hot melt adhesives
Jowat-Toptherm® | PO hot melt adhesives
Jowatherm-Reaktant® | PUR hot melt adhesives
Jowat® | flushing agent



TECHNICAL DATA
APPLICATION LIST - ADHESIVES



www.jowat.com

		Hot melt adhesives														
		EVA										PO	PUR			
		Jowatherm® 280.30	Jowatherm® 280.50 / 280.58	Jowatherm® 281.40 / 281.48	Jowatherm® 288.10	Jowatherm® 288.60	Jowatherm® 288.70	Jowatherm® 284.70	Jowatherm® 286.30	Jowatherm® 286.60	Jowatherm® 286.80	Jowat-Toptherm® 237.10	Jowatherm-Reaktant® 608.00	Jowatherm-Reaktant® 607.40	Jowatherm-Reaktant® 607.50	
Delivery Form	GRANULATE	●	●	●	●	●	●	●				●	●	●	●	●
	CARTRIDGE "CLASSIC"								●	●	●		●	●	●	●
	CARTRIDGE "GLU JET 2K"												●	●	●	●
Colour / Appearance	TRANSPARENT	●	●	●				●				●				
	LIGHT BEIGE		●	●	●	●	●	●	●	●	●	●	●	●	●	
	WHITE	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	BROWN					●		●		●	●					
	BLACK					●		●		●	●					
Straight Edgebanding	MELAMINE	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	ABS, PP, PVC ≤ 2 mm	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	ABS, PP, PVC > 2 mm	⊙	●	●	⊙	⊙	⊙		⊙	⊙	⊙	●	⊙	⊙	●	●
	LAMINATES (HPL, CPL)	●	●	●	⊙	⊙			⊙	⊙	⊙	●	●	⊙	⊙	●
	SOLID WOOD	⊙	●	●	⊙	⊙			⊙	⊙	⊙	●	⊙	⊙	●	●
	VENEER FLEECEBACKED	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	THICKVENEER	⊙	●	●	⊙	⊙	⊙		⊙	⊙	⊙	●	⊙	⊙	●	●

● Technically preferred / Available
⊙ Technically convenient

last updated: 09/2017

Please find any suggestions for processing and cleaning in the technical data sheet! Upon request!
Product availability might differ by region. Please contact us.

First class bonding



Jowat SE · Ernst-Hilker-Str. 10 - 14 · 32758 Detmold · Deutschland · Telefon: +49 (0)5231 749-0 · info@jowat.de · www.jowat.com