

Pafra Adhesives Ltd Bentalls, Basildon, Essex, SS14 3BU

Telephone +44 (0) 1268 290610

Fax +44 (0) 1268 290619
Email enquiries@pafra.com
Website www.pafra.com

AquaPAL® 9472 Tube Winding Adhesive

Issue 8 02/11/2016

AquaPAL® 9472 is a Poly(Vinyl Acetate) based adhesive specifically developed for the tube winding market where the adhesive is applied by roller or cascade systems. The adhesive is medium viscosity and has a fast wet grab to prevent edge lift and allow fast production speeds.

AquaPAL® 9472 was developed for use in food packaging; please refer to our Food Contact Status Declaration for more information.

Features & Benefits

- Medium viscosity
- Fast setting speed
- Fast grab speed
- Hard tubes
- Good mileage

Technical Data

 Viscosity:
 24.0 - 30.0 Poise @11.8 sec⁻¹
 pH:
 5.0

 Solids:
 26.0 - 29.0% sg (20 °C)
 1.04

 Brookfield 3/20/25:
 2850 centiPoise
 Colour:
 White

Application Details

AquaPAL® 9472 is designed specifically for use with roller coater or cascade/scraper systems. The adhesive should be applied at between 15-25 °C.

Storage & Shelf Life

For optimum performance use within 4 Months. Store between 5-30 °C and protect from freezing. Stir or shake before use.

Health & Safety

Users should familiarise themselves with the safety data sheet before using or handling this product.

Regulatory

Every precaution has been taken in the design of this adhesive to ensure it safe for the consumer.

Tel: +353(0)1-885 00 00

www.ectadhesives.com

info@ect.ie



