



Pafra Adhesives Ltd  
Bentalls, Basildon,  
Essex, SS14 3BU

Telephone +44 (0) 1268 290610  
Fax +44 (0) 1268 290619  
Email [enquiries@pafra.com](mailto:enquiries@pafra.com)  
Website [www.pafra.com](http://www.pafra.com)

## AquaPAL® 9510 PVA Adhesive

Issue 8 30/10/2013

AquaPAL® 9510 is a versatile cost effective PVA adhesive with a very fast grab which is easy to clean and offers good mileage. It has been designed for the corrugated packaging, bag manufacture and tube winding markets.

For corrugated packaging it suitable for application via wheel, extrusion and ball valve. Its fast grab makes it suitable for general manufacture of plain paper products.

AquaPAL® 9510 is used in paper bag making for both side seams, applied by wheel or ball valve, and bottom seams applied by stencil.

The very fast wet grab of this product makes it ideal for reducing tailing in tube winding at high speeds. Cascade applicators must be adjusted to obtain optimum coat weight allowing maximum machine speeds. It is only suitable for applications where water content is not important.

### Features & Benefits

- Fast machine speed
- Fast grab speed
- Easy clean
- Good mileage
- Cost effective
- Minimum tailing (tubes)
- Stiff Cores

### Technical Data

Viscosity:	12.0-16.0 Poise @50.7 sec <sup>-1</sup>	pH:	5.5
Solids:	25.0 - 28.0%	sg (20 °C)	1.03
Brookfield 3/20/25:	1400 centiPoise	Colour:	White

### Application Details

AquaPAL® 9510 is designed specifically for use with wheel, cascade, extrusion, and ball valve systems.

### Storage & Shelf Life

For optimum performance use within 4 Months of date of manufacture. Store between 5-30 °C and protect from freezing. Stir or shake before use.

### Health & Safety

Users should familiarise themselves with the safety data sheet before using or handling this product.

### Regulatory

Every precaution has been taken in the design of this adhesive to ensure it safe for the consumer.

Tel: +353(0)1-885 00 00

[www.ectadhesives.com](http://www.ectadhesives.com)

[info@ect.ie](mailto:info@ect.ie)

Recommendations and suggestions for the use of our materials are based on our best experience and knowledge and intended to serve as a guide only. Customers should satisfy themselves by appropriate trials that products are suitable for their applications. The Pafra Adhesives logo, AquaPAL® and ThermoPAL® are all trademarks of Pafra Adhesives Ltd.



Pafra Adhesives Ltd's registered office: 145-147 St John Street, London, EC1V 4PY.  
The Company is registered in England: No. 644949 and for VAT, registration: No. GB 250 4895 54