



Pafra Adhesives Ltd
Bentalls, Basildon,
Essex, SS14 3BU

Telephone +44 (0) 1268 290610
Fax +44 (0) 1268 290619
Email enquiries@pafra.com
Website www.pafra.com

AquaPAL® 9697 General Purpose Adhesive

Issue 6 22/07/2014

AquaPAL® 9697 is a premium VAE based adhesive developed as an all purpose fast setting, high adhesion adhesive for the assembly market where the adhesive is applied by brush or roller. It has good adhesion to a wide range of materials and difficult surfaces. It can be used for laminating plastic films, foils and Styrofoam to porous surfaces such as

Features & Benefits

- Excellent adhesion to difficult surfaces
- Good mileage
- High Viscosity
- Multipurpose

board and wood. AquaPAL® 9697 has found applications in manufacture of flight cases, under floor heating and lacquered furniture assembly.

AquaPAL® 9697 was developed for use in food packaging, please refer to our Food Contact Status Declaration for more information.

Technical Data

| | | | |
|---------------------|---|------------|-------|
| Viscosity: | 31.0 – 57.0 Poise @11.8 sec ⁻¹ | pH: | 4.0 |
| Solids: | 55.0 – 58.0% | sg (20 °C) | 1.05 |
| Brookfield 5/20/25: | 6000-11000 centiPoise | Colour: | White |

Application Details

AquaPAL® 9697 is designed for application by brush or roller. The adhesive should be applied at between 15-25 °C.

Storage & Shelf Life

For optimum performance use within 6 Months. Store between 5-30 °C and protect from freezing. Stir or shake before use.

Health & Safety

Users should familiarise themselves with the safety data sheet before using or handling this product.

Regulatory

Every precaution has been taken in the design of this adhesive to ensure it safe for the consumer.

Tel: +353(0)1-885 00 00

www.ectadhesives.com

info@ect.ie

Recommendations and suggestions for the use of our materials are based on our best experience and knowledge and are intended to serve as a guide only. Customers should satisfy themselves by appropriate trials that products are suitable for their applications. Pafra Adhesives Ltd shall not be liable for any defects in our products or any other liabilities which you may suffer which arise from a failure on your part to follow our instructions as set out in this technical data sheet. The Pafra Adhesives logo, AquaPAL® and ThermoPAL® are all trademarks of Pafra Adhesives Ltd.



Pafra Adhesives Ltd's registered office: 145-147 St John Street, London, EC1V 4PY.
The Company is registered in England: No.644949 and for VAT, registration: No. GB 250 4895 54.