

Pafra Adhesives Ltd Bentalls, Basildon, Essex, SS14 3BU

Telephone Fax Email Website +44 (0) 1268 290610 +44 (0) 1268 290619 enquiries@pafra.com www.pafra.com

# AquaPAL® 9731G Premium Jetting Adhesive

Issue 3 28/10/2016

AquaPAL® 9731G is a premium jetting adhesive specifically developed for the carton converting and corrugated packaging markets. It contains a green UV additive so that it can seen by UV detection designed to differentiate the adhesive from blue optical brighteners used in board manufacture.

AquaPAL® 9731G offers exceptional clean running and is very resistant to drying on nozzle tips whilst giving an excellent bond to both plain and coated boards. It can be used to gain deeper fiber tear with Kraft liner paper or where clay coat stripping is a problem.

#### **Benefits**

- Exceptional clean running
- Excellent bond to difficult liner papers and coated boards
- ☐ Supreme spotting and lining performance
- ☐ High penetration for clay coated boards
- Green UV active

#### **Technical Data**

 Viscosity:
 2.70-3.30 Poise @125.0 sec<sup>-1</sup>
 pH:
 ~4.6

 Solids:
 47.0 - 52.0%
 sg (20 °C)
 1.07

 Brookfield 2/20/25:
 550 centiPoise
 Colour:
 Pale Green

#### **Application Details**

AquaPAL® 9731G is designed specifically for use in low pressure jetting systems and WH Leary high pressure systems.

### Storage & Shelf Life

For optimum performance use within 6 Months. Store between 5-30 °C and protect from freezing. Stir or shake before use.

#### **Health & Safety**

Users should familiarise themselves with the safety data sheet before using or handling this product.

## Regulatory

Every precaution has been taken in the design of this adhesive to ensure it safe for the consumer.

Tel: +353(0)1-885 00 00

www.ectadhesives.com

info@ect.ie





