



Pafra Adhesives Ltd
Bentalls, Basildon,
Essex, SS14 3BU

Telephone +44 (0) 1268 290610
Fax +44 (0) 1268 290619
Email enquiries@pafra.com
Website www.pafra.com

AquaPAL® 9600 Premium Carton & Case Making Adhesive

Issue 8 21/01/2019

AquaPAL® 9600 is a premium jetting adhesive specifically developed for the carton converting and casemaking markets. It contains an additive so that it can be used in conjunction with UV detectors.

AquaPAL® 9600 offers exceptional clean running, and is very resistant to drying on nozzle tips. This is especially useful with multi gun arrangements.

AquaPAL® 9600 gives an excellent bond to both plain, clay coated and PE coated boards and also Metpol laminated boards. It can be used to gain deeper fiber tear with Kraft liner paper or where clay coat stripping is a problem.

Features & Benefits

- Exceptional clean running
- Excellent bond to difficult liner papers & coated boards
- Excellent spotting & lining performance
- UV active
- Good bond to difficult surfaces including Metpol

Technical Data

Viscosity:	3.50-4.10 Poise @ 125 sec ⁻¹	pH:	3.7
Solids:	46.0 - 51.0%	sg (20 °C)	1.03
Brookfield 2/20/25:	950 centiPoise	Colour:	White

Application Details

AquaPAL® 9600 is designed specifically for use with low and high pressure jetting systems and medium size ball valve applicators.

Storage & Shelf Life

For optimum performance use within 9 Months of date of manufacture. Store between 5-30 °C and protect from freezing. Stir or shake before use.

Health & Safety

Users should familiarise themselves with the safety data sheet before using or handling this product.

Regulatory

Every precaution has been taken in the design of this adhesive to ensure it safe for the consumer.

Tel: 01 – 885 00 00

www.ect.ie

info@ect.ie

Recommendations and suggestions for the use of our materials are based on our best experience and knowledge and intended to serve as a guide only. Customers should satisfy themselves by appropriate trials that products are suitable for their applications. The Pafra Adhesives logo, AquaPAL® and ThermoPAL® are all trademarks of Pafra Adhesives Ltd.



Pafra Adhesives Ltd's registered office: 145-147 St John Street, London, EC1V 4PY.
The Company is registered in England: No.644949 and for VAT, registration: No. GB 250 4895 54