



Pafra Adhesives Ltd
Bentalls, Basildon,
Essex, SS14 3BU

Telephone +44 (0) 1268 290610
Fax +44 (0) 1268 290619
Email enquiries@pafra.com
Website www.pafra.com

AquaPAL® 8900 Premium Carton Side Seam Adhesive

Issue 7 06/06/2017

AquaPAL® 8900 is a premium VAE based adhesive specifically developed for the carton converting market where the adhesive is applied by wheel or extrusion. It is designed for bonding carton side seams at high line speeds up to 650 m/min without splashing with wheel applicators.

AquaPAL® 8900 gives an excellent bond to both plain and coated boards. It can be used to gain deeper fibre tear with Kraft liner paper or where clay coat stripping is a problem.

AquaPAL® 8900 was developed for use in food packaging; please refer to our Food Contact Status Declaration for more information.

Features & Benefits

- Exceptional clean running
- Excellent adhesion to plain and coated boards
- Very High machine speeds
- Deep fibre tear
- High creep resistance
- Minimal splashing
- Good mileage

Technical Data

| | | | |
|---------------------|---|-------------------|-------|
| Viscosity: | 26.0-34.0 Poise @11.8 sec ⁻¹ | pH: | 4.5 |
| Solids: | 53.5 – 57.5% | sg (20 °C) | 1.07 |
| Brookfield 4/20/25: | 4300 centiPoise | Colour: | White |

Application Details

AquaPAL® 8900 is designed specifically for use with wheel in pot and extrusion systems.

Storage & Shelf Life

For optimum performance use within 12 Months. Store between 5-30 °C and protect from freezing. Stir or shake before use.

Health & Safety

Users should familiarise themselves with the safety data sheet before using or handling this product.

Regulatory

Every precaution has been taken in the design of this adhesive to ensure it safe for the consumer.

Tel: 01 – 885 00 00

www.ect.ie

info@ect.ie

Recommendations and suggestions for the use of our materials are based on our best experience and knowledge and intended to serve as a guide only. Customers should satisfy themselves by appropriate trials that products are suitable for their applications. The Pafra Adhesives logo, AquaPAL® and ThermoPAL® are all trademarks of Pafra Adhesives Ltd.



Pafra Adhesives Ltd's registered office: 145-147 St John Street, London, EC1V 4PY.
The Company is registered in England: No.644949 and for VAT, registration: No. GB 250 4895 54