Application chart

- Official recommendation list for edgebanding
- Approved and qualified by Homag Holzbearbeitungssysteme GmbH



Jowatherm® | EVA hot melt adhesives
Jowat-Toptherm® | PO hot melt adhesives
Jowat-Hightherm® | PO hot melt adhesives
Jowatherm-Reaktant® | PUR hot melt adhesives
Jowacoll® | PVAc dispersion adhesives







TECHNICAL DATA

APPLICATION LIST - ADHESIVES



ŧ							E			Н	ot m	elt a	adhe	sive	es										PVAc	
ŧ		\vdash					E	Hot melt adhesives																		
ŧ			EVA PO PA													PUR						La				
www.jowat.com		Jowatherm® 280.30	Jowatherm® 280.40	Jowatherm® 280.50 / 280.58	Jowatherm [®] 281.40 / 281.48	Jowatherm [®] 288.10	Jowatherm® 288.60	Jowatherm® 288.70	Jowatherm® 288.80	Jowatherm® 284.00	Jowatherm® 284.70	Jowatherm® 280.10	Jowatherm [®] 261.20	Jowat-Toptherm® 237.10	Jowat-Toptherm® 237.70	Jowat-Hightherm® 227.30	Jowat-Hightherm® 223.00	Jowatherm® 211.50	Jowatherm-Reaktant® 608.00	Jowatherm-Reaktant® 607.50	Jowatherm-Reaktant® 607.60	Jowatherm-Reaktant® 606.70	Jowatherm-Reaktant® 602.30	Jowat [®] 930.94	Oracoll® 128 70	
		•	•	•	•	•	•	•	•	•	•	•		•	•	0			•	•	0	0			Γ	
ABS, PP, PVC ≤ 2 mm		•	•	•	•	•	•	•	•	•	•	•		•	•	0			•	•	•	0			Г	
ABS, PP, PVC > 2 mm LAMINATES (HPL, CPL) SOLID WOOD		0	0	•	•	0	0	0	0			•		•	0	•			0	0	0	•			Г	
S		•	0	•	•	0	0		0			•		•	0	•			•	0		•			Γ	
sorid Mood		0	0	•	•	0	0		0			•		•	0	•			0	0	0	•		(NO		
CKED		•	•	•	•	•	•	•	•	•	•	•		•	•	0			•	•	•	0		ktant® (F	Γ	
EER		0	0	•	•	0	0	0	0			•		•	0	•			0	0	0	•		em-Rea	Г	
		•	•	•	•	•	•	0	•	0	0	0		•	•				•	0	0	0		Jowathe	Γ	
S (CPL)		0	0	•	•	0	•		•					•	0				•		0	0		Flushing agent Jowatherm-Reaktant® (PUR)		
LAMINATES (CPL) VENEER FLEECEBACKED		•	•	•	•	•	•	0	•	0	0	0		•	•		4		•	0	•	0		Flushing		
5 m/min		•		•	•	•	•	•	0	0	0	0							•	•	•	0			Γ	
0 m/min		0	•	•	•	•	•	•	•	•	•	•		•	•	0			0	•	•	0			t	
\$ 60 m/min > 60 m/min			•	•	•				0					0	•					0	0				İ	
		0		•	•							•		0		•			0		0	•			Ē	
																0	•	•				0			t,	
G)													•					•							T	
3)							_					\vdash						Н					\vdash	\vdash	t	
														•	•	•										

Please find any suggestions for processing and cleaning in the technical data sheet (upon request)! Product availability might differ by region. Please contact us.

Tel: 01-8850000 www.ect.ie



