

50ml 1:1/2:1 Two-component Sealant Caulking Gun



Product Description:

Item no.: KS1-50ml1:1/2:1 Caulking Gun

Cartridge: two-component

Capacity: 50ml (1:1/2:1)

Material: Reinforced Nylon & Metal Alloy

Weight: 0.286kg / piece

Package:50pcs/ctn

Dimension: 610*420*400mm

Instructions:

1. Open the swift of handle and then pull the rack to reach the maximum.
2. Put chemical material into two-component cartridge.
3. Promote the trigger to make the chemical material come out smoothly from the cartridge
4. After using, put the rack back to the original location.
5. Remove the cartridge, then to repeat the above operation.

Our plastic caulking guns have 2 strong points :

1. Long service life: Life duration is 5 times more than iron caulking gun.
- 2 High-efficiency:The force is up to 450kg-500kg and save your strength 5 times more than common iron caulking gun.

Brake Release

Push the brake handle forward to release the drive rod and to remove the piston pressure.

Cleaning & Maintenance

It is very important to keep the drive rod clean and to oil it frequently in order to ensure a better function.

Recover the Movement of the Piston

Symptom: Back-lash of the brake

Remedy: Turn the adjusting screw clockwise the whole way down until the drive rod can be moved back and forth.

To eliminate the back-lash, which may occur after many operations, follow the instructions below:

Turn the adjusting screw counter-clockwise until the drive rod can be exactly moved back and forth.



1. Cartridge Slot



2. Push Piston



3. Lock Switch for the push rod



4. The push rod

