

# Application Chart

- Edgebanding
- List of suggestions for product selection
- Approved and qualified by Fraval



**Jowatherm® | EVA hot melt adhesives**

**Jowat-Hightherm® | PO hot melt adhesives**

**Jowatherm-Reaktant® | PUR hot melt adhesives**

**Jowat® | Flushing agent**



www.jowat.com

		Hot melt adhesives														Jowat® 930.74 / 930.94				
		EVA												PO	PUR					
		Jowatherm® 280.00	Jowatherm® 280.10	Jowatherm® 280.30	Jowatherm® 280.50 / 280.58		Jowatherm® 281.40	Jowatherm® 288.10	Jowatherm® 288.60	Jowatherm® 288.70	Jowatherm® 284.70	Jowatherm® 282.40	Jowatherm® 282.20	Jowatherm® 282.60	Jowat-Hightherm® 221.00		Jowatherm-Reaktant® 608.00	Jowatherm-Reaktant® 607.40	Jowatherm-Reaktant® 607.50	
Straight edgebanding	MELAMINE	●	○	●	○	○	○	○	○	○	○	○	○	○	●	●	●	●	Flushing agent   Jowatherm-Reaktant® (PUR)	
	ABS, PP, PVC ≤ 2 mm	●	●	●	●	●	●	●	○	○	○	○	○	○	●	●	●	●		
	ABS, PP, PVC > 2 mm	○	●	○	○	○	○	○						○	○	○	○	○		
	LAMINATES (HPL)	○	○	○	○	○	○	○				○	○	○	○	●	○	○		○
	SOLID WOOD ≤ 8 mm	○	●	○	○	○	○	○						○	○	○	○	○		○
	VENEER FLEECEBACKED	●	○	●	○	○	○	○	○	○	○	○	○	○	●	●	●	●		●
	MULTI-LAYER VENEER	○	●	○	○	○	○	○						○	○	○	○	○		○
Colour / Appearance	TRANSPARENT	●	●	●	●						●			●	●					
	LIGHT BEIGE				●	●	●	●	●	●		●	●			●	●	●		
	WHITE		●	●	●		●	●	●	●		●	●		●	●	●	●		
	BROWN							●		●										
	BLACK							●		●										
PUR granulate															●	●	●			
Feed speed	≤ 14 m/min	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○		
	10 - 25 m/min	●	●	●	●	●	●	●	●	●	○	○	○	○	○	○	○	○		
Manual edgebander		○	●	○	●	●					●	○	○		●	○	○			
● Technically preferred / available ○ Technically possible																				

last updated: 08/2019

The information given in this leaflet is based on test results from our laboratories as well as on experience gained in the field, and does in no way constitute any guarantee of properties. Due to the wide range of different applications, substrates, and processing methods beyond our control, no liability may be derived from these indications nor from the information provided by our free technical advisory service. Before processing, please request the corresponding data sheet and observe the information in it! Customer trials under everyday conditions, testing for suitability at normal processing conditions, and appropriate fit-for-purpose testing are absolutely necessary. For the specifications as well as further information, please refer to the latest technical data sheets. Product availability might differ by region. Please contact us.