

Application Chart

- Edgebanding
- List of suggestions for product selection
- Approved and qualified by Holz-Her GmbH




Jowatherm® | EVA hot melt adhesives
Jowat-Toptherm® | PO hot melt adhesives
Jowatherm-Reaktant® | PUR hot melt adhesives
Jowat® | Flushing agent



TECHNICAL DATA

APPLICATION LIST - ADHESIVES



 www.jowat.com		Hot melt adhesives											Jowat® 930.74 / 930.94	
		EVA										PO		PUR
		Jowatherm® 280.30	Jowatherm® 280.50 / 280.58	Jowatherm® 281.40	Jowatherm® 288.10	Jowatherm® 288.60	Jowatherm® 288.70	Jowatherm® 284.70	Jowatherm® 286.30	Jowatherm® 286.60	Jowatherm® 286.80	Jowat-Toptherm® 237.10		Jowatherm-Reaktant® 607.40
Delivery Form	GRANULATE	●	●	●	●	●	●	●			●	●	●	●
	CARTRIDGE "CLASSIC"								●	●	●		●	●
	CARTRIDGE "GLU JET 2K"											●	●	●
Colour / Appearance	TRANSPARENT	●	●							●				
	LIGHT BEIGE		●	●	●	●	●	●		●	●	●		
	WHITE	●	●		●	●	●	●	●	●	●	●		
	BROWN					●		●		●	●			
	BLACK					●		●		●	●			
Straight edgebanding	MELAMINE	●	○	○	○	○	○	○	●	○	○	○	●	●
	ABS, PP, PVC ≤ 2 mm	●	●	●	●	●	○	○	●	●	●	●	●	●
	ABS, PP, PVC > 2 mm	○	○	○	○	○	○		○	○	○	○	○	○
	LAMINATES (HPL)	○	○	○	○	○			○	○	○	○	○	○
	SOLID WOOD ≤ 8 mm	○	○	○	○	○			○	○	○	○	○	○
	VENEER FLEECEBACKED	●	○	○	○	○	○	○	●	○	○	○	●	●
	MULTI-LAYER VENEER	○	○	○	○	○	○		○	○	○	○	○	○
Flushing agent Jowatherm-Reaktant® (PUR)														
● Technically preferred / available ○ Technically possible														

last updated: 08/2019

The information given in this leaflet is based on test results from our laboratories as well as on experience gained in the field, and does in no way constitute any guarantee of properties. Due to the wide range of different applications, substrates, and processing methods beyond our control, no liability may be derived from these indications nor from the information provided by our free technical advisory service. Before processing, please request the corresponding data sheet and observe the information in it! Customer trials under everyday conditions, testing for suitability at normal processing conditions, and appropriate fit-for-purpose testing are absolutely necessary. For the specifications as well as further information, please refer to the latest technical data sheets. Product availability might differ by region. Please contact us.