



6092 ADHESIVE

SOLVENT BASED ADHESIVE

KEY FEATURES

- Bonds a variety of soling materials
- No adhesive thickening in through-feed sole cementing machines
- Long tack retention time

DESCRIPTION

Bostik 6092 is a brushable, solvent-borne adhesive based on polychloroprene rubber.

RECOMMENDED USE

Bostik 6092 is primarily used for shoe sole attaching and has been specifically developed to overcome the problem of adhesive thickening in through-feed sole cementing machines when used intermittently.

Bostik 6092 is suitable for use on resin rubber, microcellular and composition rubber soling materials. It is also suitable for leather soles but in this case the application of two coats of adhesive is advised.

To obtain the best results with **Bostik 6092** for sole attaching it should be used in conjunction with **Bostik 6090** applied to the shoe uppers.

IMPORTANT

Before embarking on any work involving **Bostik 6092** the safety data sheet should be carefully studied by those carrying out the work.

METHOD OF USE

APPLICATION & BONDING

- Apply **Bostik 6092** by through-feed sole cementing machine or by brush and allow to dry.
- Reactivate the dried adhesive film by one way heat to 90°C, preferably by the use of a suitable sole heat activating unit, and effect bonding.
- A tack retention time of 10 days can be obtained allowing uppers to be cemented over the weekend

TACK RETENTION TIMES

Minimum prior to stacking	30 min
Minimum prior to sole attaching	4 hours
Maximum on soles (soles heated)	10 days
Maximum on soles (upper heated)	3 days

TYPICAL CHARACTERISTICS

Physical form	Semi-viscous liquid
Colour	Off white
Odour	Ketonic
Chemical type	Polychloroprene rubber/resin blend
Solvent	Mixture of light petroleum spirit, ketone and toluene
Flammability	Highly flammable
Flash point [closed cup]	In the group -18 to -7°C
Viscosity Brookfield RVT 20rpm at 25°C [P]	Approx. 28
Total solids content [%]	Approx. 24
Relative density	Approx. 0.86
Cleaner	Bostik Cleaner/Thinner M501 for cleaning application equipment

BSI STANDARDS



FM 01696
BS EN ISO 9001:2008

PACKAGING

For current pack sizes please contact the Customer Service Department.

STORAGE

Store in a cool, dry, well ventilated flame proof area in the temperature range 5 - 25°C.

SHELF LIFE

At least 12 months closed in original container stored under the above conditions.

Disclaimer – please read carefully

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products..

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, or its liability for fraud, or fraudulent misrepresentation, or any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including

in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company. Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number on the bottom right hand side of this page.

SMART HELP

Please contact your local representative

